

GMT221 and GMT222 CO₂ Transmitters

Vaisala CARBOCAP® CO ₂ Transmitter		GM	T	22															PRICE
Measurement range (GMT221)	0...2 %CO ₂	1	H																
	0...3 %CO ₂	1	J																
	0...5 %CO ₂	1	K																
	0...10 %CO ₂	1	L																
	0...20 %CO ₂	1	M																
(GMT222)	0...2000 ppmCO ₂ adjusted at 1000 ppm (*)	2	B																
	0...2000 ppmCO ₂	2	C																
	0...3000 ppmCO ₂	2	D																
	0...5000 ppmCO ₂	2	E																
	0...7000 ppmCO ₂	2	F																
	0...10000 ppmCO ₂	2	G	0															
Probe installation accessories	none <i>mounting clips, 2 pcs</i> <i>mounting flange</i>																		
Field check adapter	none <i>adapter</i>																		
Display on cover	LED lights only <i>LED lights + backlit digital LCD display</i>																		
Wall/remote use	probe in transmitter (wall model) <i>probe with cable (remote installation of probe)</i> <i>probe with 10 m cable (remote installation of probe)</i>																		
Alarm relay 1	setpoint not activated custom setpoint for relay 1 _____ ppm / % CO₂																		
	Example: custom setpoint for relay 1 <u>1000</u> ppm / % CO ₂ -> Relay will be activated above 1000 ppm CO ₂																		
Alarm relay 2	setpoint not activated custom setpoint for relay 2 _____ ppm / % CO₂																		
	Example: custom setpoint for relay 2 <u>4</u> ppm / % CO ₂ -> Relay will be activated above 4% CO ₂																		
Accessories	none <i>serial COM adapter (19040GM)</i>																		
Manual	No manual English Japanese																		
TOTAL																			
QTY																			
TOTAL VALUE																			

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

(* special accuracy specification)

Examples of order codes with typical settings:

Transmitter **GM T 22 1 L 0 N 0 B 0 N 1 A 0 B**

End customer: _____