Order form
Purchaser

_____

Valid from January 2006
Order no.

_____

HMT100 Series Humidity and Temperature Transmitter

Vaisala HUMICAP® Humidity and Temperature Transmitter Series	**HMT100**																							**Price**
Transmitter type	**Wall mount/fixed probe**																							
	Remote probe with 3 m cable																							
	Remote probe with 5 m cable																							
	Remote probe with 10 m cable																							
	Remote probe with 10 m cable + 10 m extension																							
Display	**No display**																							
	*Display *)*																							
Output channels	**RH or Td output only**																							
	Two output parameters																							
Signal output	**4...20 mA**	**2-wire loop-powered**																						
	0...1 V	**3-wire**																						
	0...5 V	**3-wire**																						
	0...10 V	**3-wire**																						
SPECIAL	**Define scale:**	**3-wire**	**0...**	_____	**V **)**																			
Parameter for Ch1	**RH**	**0...100 %RH**																						
	Td	**-20...80 °C**	**(-4...+176 °F)**																					
SPECIAL	**Define quantity**	_____	**Scale**	_____																				
Parameter for Ch2	**No**																							
	T	**-40...+60 °C**	**(-40...+140 °F)**																					
		-20...+80 °C	**(-4...+176 °F)**																					
		0...+60 °C	**(32...+140 °F)**																					
		-40...+80 °C	**(-40...+176 °F)**																					
		0...+50 °C																						
SPECIAL	**Define scale**	_____																						
Output units	**Metric**																							
	Non metric																							
Humidity sensor type	**General purpose**																							
Sensor protection	**Plastic grid**																							
	Plastic grid with filter																							
	Stainless steel sintered filter (only with remote probes)																							
Transmitter installation	**No accessories**																							
	Wall mounting plate (Aluminum)																							
	Outdoor installation kit (Weather shield)																							
Installation kit for probe	**No accessories**																							
	Duct installation kit																							
	DTR502B with probe installation kit																							
	Probe installation kit for DTR502																							
Cable bushings	**Cable gland for 2...6 mm cable**																							
	Conduit fitting PG9																							
	Conduit fitting NPT 1/2"																							
Operation manual language	**No manual**																							
	English																							
	Japanese																							
																							Total	
																							QTY	
																							Total value	

*) display backlight not possible with 4...20 mA output
**) value must be between 0...10 V

Selections in bold are included in the prices of the basic versions
Selections in italic are available at an extra cost

Example of order code with typical settings

HMT100	**A**	**0**	**2**	**A**	**1**	**2**	**1**	**A**	**2**	**A**	**1**	**A**	**A**	**0**	**0**